



FOR IMMEDIATE RELEASE

SlimVent™ Obround Grease Duct Achieves UL 2221 Classification

Bettendorf, Iowa (January 31, 2011) – Schebler Chimney Systems SlimVent™ obround grease duct is now UL 2221 Classified for zero-clearance to combustibles carrying a 2-hour fire rating.

SlimVent's revolutionary patented design makes it ideal for grease duct installations where round products do not meet overhead clearances, providing up to 28% space savings. Additionally, the duct's straight side design makes it a safer alternative to field-fabricated, non-UL listed rectangular ducts.

SlimVent™ features 4 inches of high temperature ceramic fiber insulation and is available with a 304 or 316 stainless inner liner and the choice of a 304, 316 stainless or aluminized outer shell. Sections are joined by the proven ½" flange-to-flange "V" band connection creating a pressure-tight, leak-free, non-welded joint.

All Schebler prefabricated models are available for shipping within two weeks, considerably faster than the industry standard. Product gets to the job site quicker which eliminates costly work stoppages.

For more information, call 800.391.0009 or visit www.scheblerchimney.com.

###

Schebler Chimney Systems manufactures and installs prefabricated chimneys, vents and grease ducts for a wide variety of industries.

Product Inquiries:

Mike Mommsen

Schebler Chimney Systems

(563) 459-6823

mmommsen@schebler.com

Media Inquiries:

Felicia Wyrick

Adfinity Marketing Group

(319) 363-3338

fwyrick@adfinitymarketing.com